

Preliminary data sheet

RF Power Amplifier

RF0011000-25 bi

This solid state power amplifier is designed for reliable, trouble-free service. It operates in a class A/AB and includes RF protection circuits, cooling installations and 230 V AC power supply. The amplifier is accommodated in a 19" system housing.

Features :

- * 25 to 30 Watts saturated output power
- * 40 dB minimum gain
- * Electronic Attenuator in option
- * Temperature protection

Applications :

- * Test Bench
- * Field Test
- * Instrumentation

Specifications

Characteristics	Data	Units
Frequency range band 1	0.01 - 240	MHz
band 2	180 - 1000	MHz
RF output power CW		
Typ.	25	W
Min	20	W
Class	A/AB	
Power gain	43	dB
Flatness typ	+/-2,5 dB	dB
Input power for rated output power	0	dBm
Max. input power	7	dBm
In / Out impedances nom.	50	Ohms
Input VSWR	2 : 1	
Load VSWR for rated output power	up to 1.5 : 1	
VSWR mismatch	infini à 25 W	
Protection circuits	Over temperature	
Harmonics typ.	-15	dBc
Spurious typ.	-60	dBc
Modulation capability	100	%
Noise Figure typ.	10	dB
Intercept point 3 rd Order min.		dBm
RF connectors	N female	
Cooling	Forced air (self-contained fans)	
Operating temperature Range	0 °C ... + 40	° C
Power Supply	230 AC +/- 10 % ,47-63 Hz	V
Dimensions (W x L x H)	4 U 19" Rack 490 x 460 x 172	mm
All data at room temperature + 22 °C, into 50 Ohms, subject to change without notice		

Made in European Union

11/07/2001

R.F.P.A. S.A.

Parc d'activité de Fontaudin F33370 Artigues près Bordeaux
 France Tél : +33 (0)5 56 86 85 84 Fax: + 33 (0) 5 56 86 55 56