

Preliminary data sheet

# RF Power Amplifier

RF001220 - 10

This solid state power amplifier is designed for reliable, trouble-free service. It operates in a class A/AB and includes RF protection circuits, cooling installations so as a 230 V AC power supply. The amplifier is accommodated in a 19" system housing.

**Features :**

- \* 15 Watts saturated output power
- \* 40 dB minimum gain
- \* Electronic Attenuator in option
- \* Temperature protection

**Applications :**

- \* RF links
- \* Tests Bench
- \* Fields Test
- \* Instrumentations

**Specifications**

Characteristics	Data	Units
Frequency range	0,01 - 220	MHz
RF output power CW		
Typ.	15	W
Min	10	W
Class	A / AB	
Power gain	37	dB
Flatness	+/-2,5 dB	dB
Input power for rated output power	0	dBm
Max. input power	13	dBm
In / Out impedances nom.	50	Ohms
Input VSWR	2 : 1	
Load VSWR for rated output power	up to 1.5 : 1	
VSWR mismatch	5 : 1 @ 10 W	
Protection circuits	Load VSWR, over temperature	
Harmonics typ.	-20	dBc
Spurious typ.	-60	dBc
Modulation capability	100	%
Noise Figure typ.	10	dB
Intercept point 3 rd Order typ.		dBm
RF connectors	N female	
Cooling	Forced air (self-contained fans)	
Operating temperature Range	0 °C ... + 40	° C
Power Supply	230 AC +/- 10 % ,47-63 Hz	V
Dimensions (W x L x H)	3 U 19" Rack 490 x 360 x 132	mm

All data at room temperature + 22 °C, into 50 Ohms, subject to change without notice