

# RF Power Amplifier

## RF120250 - 250

This solid state power amplifier is designed for reliable, trouble-free service. It operates in a class A/AB and includes RF protection circuits, cooling installations and 230 V AC power supply. The amplifier is accommodated in a 19" system housing.

### Features :

- \* 280 Watts saturated output power
- \* 53 dB minimum gain
- \* Electronic Attenuator in option
- \* Meter in option
- \* Temperature protection
- \* RS232 or RS485 or IEEE in option



### Applications :

- \* RF links
- \* Test Bench
- \* Field Test
- \* Instrumentation

### Specifications

case : RAC008-02

Characteristics	Data	Units
Frequency range	120 - 250	MHz
RF output power CW		
Typ.	260	W
Min	250	W
Class	A / AB	
Power gain	50	dB
Flatness	+/-2,5 dB	dB
Input power for rated output power	0	dBm
Max. input power	13	dBm
In / Out impedances nom.	50	Ohms
Input VSWR	2 : 1	
Load VSWR for rated output power	up to 1.7 : 1	
VSWR mismatch	infinite @ 200 W power decrease	
Protection circuits	Load VSWR, over temperature	
Harmonics typ.	-20	dBc
Spurious typ.	-60	dBc
Modulation capability	100	%
Noise Figure typ.	10	dB
Intercept point 3 rd Order typ.		dBm
RF connectors	N female	
Cooling	Forced air (self-contained fans)	
Operating temperature Range	0 °C ... + 40	° C
Power Supply	230 AC +/- 10 % ,47-63 Hz	V
Dimensions (W x L x H)	RAC008-02 4 U p 460 mm	
All data at room temperature + 22 °C, into 50 Ohms, subject to change without notice		