

# RF Power Amplifier

## RF28-32 P

This solid state power amplifier is designed for reliable, trouble-free service. It operates in class A and includes RF protection circuits, fan cooling, and a 230 V AC power supply. The amplifier is accommodated in a 19" system housing.

### Features :

- \* 2,5 to 3 Watts saturated output power
- \* 32 dB minimum gain

- \* Temperature protection

### Applications :

- \* Microwaves links
- \* Test bench
- \* Field testing
- \* Instrumentation



Case : RAC006-01

### Specifications

Characteristics	Data	Units
Frequency range	2000 - 8000	MHz
RF output power CW		
Typ.	2,5	W
Min	2	W
Class	A	
Power gain	33	dB
Flatness	+/-2,5 dB	dB
Input power for rated output power	0	dBm
Max. input power	13	dBm
In / Out impedances nom.	50	Ohms
Input VSWR	2 : 1	
Load VSWR for rated output power	up to 1.5 : 1	
VSWR mismatch	5:1 @ 2 W	
Protection circuits	Over temperature	
Harmonics typ.	-15	dBc
Spurious typ.	-60	dBc
Modulation capability	100	%
Noise Figure typ.	10	dB
Intercept point 3 rd Order min.	40	dBm
RF connectors	N female	
Cooling	Forced air (self-contained fans)	
Operating temperature Range	0 °C ... + 40	° C
Power Supply	230 AC +/- 10 % ,47-63 Hz	V
Dimensions (W x L x H)	RAC006-1	
All data at room temperature + 22 °C, into 50 Ohms, subject to change without notice		

Made in European Union

16/10/2001

### R.F.P.A. S.A.

Parc d'activité de Fontaudin F33370 Artigues près Bordeaux  
France Tél : +33 (0)5 56 86 85 84 Fax: + 33 (0) 5 56 86 55 56