

**Preliminary data sheet**

# RF Power Amplifier

# RF9002000-50

This solid state power amplifier is designed for reliable, trouble-free service. It operates in a class A and includes RF protection circuits, cooling installations so as a 230 V AC power supply. The amplifier is accommodated in a 19" system housing.

**Features :**

- \* 50 to 60 Watts saturated output power
- \* 43 dB minimum gain
- \* Electronic Attenuator in option 1
- \* Power indicator via RS232 in option 2
- \* LCD display with alarm and total remote control in option 3
- \* Temperature protection

**Applications :**

- \* Microwaves links
- \* Tests Bench
- \* Fields Test
- \* Instrumentations

**Specifications**

Characteristics	Data	Units
Frequency range	900 - 2000	MHz
RF output power CW		
Typ.	60	W
Min	50	W
Class	A	
Power gain	47	dB
Flatness	+/- 2 dB	dB
Input power for rated output power	0	dBm
Max. input power	13	dBm
In / Out impedances nom.	50	Ohms
Input VSWR	2 : 1	
Load VSWR for rated output power	up to 1.5 : 1	
VSWR mismatch	8:1 à 50 W	
Protection circuits	Over temperature	
Harmonics typ.	-15	dBc
Spurious typ.	-60	dBc
Modulation capability	100	%
Noise Figure typ.	10	dB
Intercept point 3 rd Order min.	55	dBm
RF connectors	N female	
Cooling	Forced air (self-contained fans)	
Operating temperature Range	0 °C ... + 40	° C
Power Supply	230 AC +/- 10 % ,47-63 Hz	V
Dimensions (W x L x H)	4 U 19" Rack 490 x 460 x 176	mm
All data at room temperature + 22 °C, into 50 Ohms, subject to change without notice		

Made in European Union

05/04/2001

**R.F.P.A. S.A.**

Parc d'activité de Fontaudin F33370 Artigues près Bordeaux  
 France Tél : +33 (0)5 56 86 85 84 Fax: + 33 (0) 5 56 86 55 56