

## Low Noise Broadband Amplifier module

# BA301000-32-40IP

This solid state Low Noise amplifier is designed for reliable, trouble-free service. It operates in a class A with a 15 V DC power supply. The amplifier is accommodated in aluminium housing.

### Features :

- \* 2,5 dB of NF
- \* 32 dB minimum gain
- \* Electronic Attenuator in option
- \* Overvoltage and reverse protection



case : B005-01

### Applications :

- \* RF links
- \* Tests Bench
- \* Fields Test
- \* Instrumentations

### Specifications

Characteristics	Data	Units
Frequency range	30 - 1000	MHz
RF output power CW		
Typ.	19	dBm
Min	17	dBm
Class	A	
Power gain typ	32	dB
Flatness	+/- 2,5 dB	dB
Input power for rated output power	-35	dBm
Max. input power	0	dBm
In / Out impedances nom.	50	Ohms
Input VSWR	2,5 : 1	
VSWR mismatch	Infinite	
Protection circuits	Over and reverse voltage	
Modulation capability	100	%
Noise Figure typ.	2,5	dB
Intercept point 3 rd Order typ.	40	dBm
RF connectors	SMA female	
Cooling	by conduction	
Operating temperature Range	0 °C ... + 55	° C
Power Supply	15 DC	V
Dimensions (W x L x H)	51 x 70 x 21 B005-01	mm
All data at room temperature + 22 °C, into 50 Ohms, subject to change without notice		

Made in European Union

28/03/2001

[WWW.rfpa.com](http://WWW.rfpa.com)

**R.F.P.A. S.A.**

Parc d'activité de Fontaudin F33370 Artigues près Bordeaux  
France Tél : +33 (0)5 56 86 85 84 Fax: + 33 (0) 5 56 86 55 56