

RF Fiberoptic link

Standalone receiver

APO 00251000-RX

This RF fiberoptic link is designed for remote RF and *pulse* signal in a wide range of frequency between 25 KHz to 1000 MHz

Features :

- * RX photodiode InGaS
- * RX alarm
- * Optical power measurement
- * extra gain (10 to 20 dB) in option
- * High output IP3
- * AGC gain in option

Applications :

- * RF and Microwave links
- * remote RF link
- * Pulse transportations non inverting
- * Instrumentations



Case : CAO 01-01

Specifications

Characteristics	Data	Units
Frequency range	25 KHz - 1000 MHz	MHz
Wavelength	1600	
Typ.	1310	nm
Min	900	
Class	A	
link gain (for 0 dBo)	+/- 2	dB
Flatness	+/- 1,5	dB
Input power for rated output power	0	dBm
Max. optical input power	10	dBo
Out impedance nom.	50 ***	Ohms
Relative intensity noise	-135	dB/Hz
Intercept point 3 rd Order typ.(link)	30	dBm
Alarm (over current and no optical)	dry loop	
Optical connectors	FC/APC *	
Fiber loss	0,4	dB/km
optical connectors loss	0,5	dB/paire
Typical RF link NF	40 **	dB
RF connectors	SMA female	
Storage temperature range	-40 °C ... + 85	° C
Operating temperature Range	-20 °C ... + 60	° C
Power Supply	12 V DC +/- 5 % I : 120 mA	
size (W x L x H)	7 F x 175 mm x 3 U	mm
All data at room temperature + 22 °C, into 50 Ohms, subject to change without notice		

* Other connectors can be mounted upon request

** a LNA can be added as a option

*** option 75 for 75 Ohms

Made in European Union

18/09/2001

www.rfpa.com

R.F.P.A. S.A.

Parc d'activité de Fontaudin F33370 Artigues près Bordeaux

France Tél : +33 (0)5 56 86 85 84 Fax: + 33 (0) 5 56 86 55 56