

RF Power Source

RFS 27 - 200

This solid state RF power source is designed for reliable, trouble-free service. It operates in a class C and includes RF protection circuits, cooling installations so as a 230 V AC power supply. The amplifier is accommodated in a 19" system housing.

Features :

- * 250 Watts saturated output power
- * including crystal oscillator
- * Power variation over more than 15 dB
- * Temperature protection

Applications :

- * RF generators
- * Power sources as a driver
- * Fields Test
- * Instrumentations

Specifications

Characteristics	Data	Units
Frequency	27,125	MHz
RF output power CW		
Typ.	220	W
Min	200	W
Class	C	
Crystal oscillator	yes	
Gain control remote	> 15	dB
External power control	0 to 10	V
Out impedance nom.	50	Ohms
Load VSWR for rated output power	up to 1.5 : 1	
VSWR mismatch	Infinite (the power decrease)	
Protection circuits	Load VSWR, overtemperature	
Harmonics typ.	-40	dBc
Spurious typ.	-60	dBc
RF ON/OFF remote	remote	
P fwd remote	0 to 10	V
P reflect remote	0 to 10	V
RF connector	N female	
Cooling	Forced air (self-contained fans)	
Operating temperature Range	0 °C ... + 40	° C
Power Supply	230 V AC	V
Dimensions (W x L x H)	4 U 19" Rack d : 460 mm	mm
All data at room temperature + 22 °C, into 50 Ohms, subject to change without notice		

remote : have to be use with a external control circuit

WWW.rfpa.com

Made in European Union

11/03/2002

R.F.P.A. S.A.

Parc d'activité de Fontaudin F33370 Artigues près Bordeaux
 France Tél : +33 (0)5 56 86 85 84 Fax: + 33 (0) 5 56 86 55 56