

RF Power Amplifier

RF20252120 -100

This solid state power amplifier is designed for reliable, trouble-free service. It operates in a class A/AB and includes RF protection circuits, cooling installations 230 V AC power supply. The amplifier is accommodated in a 19" system housing.

Features :

- * 100 Watts saturated output power
- * 50 dB minimum gain
- * Option : fully remote control by RS232 or RS485
- * Output isolator included
- * Temperature protection

Applications :

- * Microwaves links
- * Tests Bench
- * Fields Test
- * Instrumentations

Specifications

Characteristics	Data	Units
Frequency range	2025 - 2120	MHz
RF output power CW		
Typ.	120	W
Min	100	W
Class	A/AB	
Power gain min	50	dB
Flatness	+/- 1,5 dB	dB
Input power for rated output power	0	dBm
Max. input power	13	dBm
In / Out impedances nom.	50	Ohms
Input VSWR	2 : 1	
Load VSWR for rated output power	up to 1.5 : 1	
VSWR mismatch	Infinite	
Protection circuits	Load VSWR, overtemperature	
Harmonics typ.	-20	dBc
Spurious typ.	-60	dBc
option remote control	dry loop for alarm	
option 1	RS232 connection	
Modulation capability	100	%
Noise Figure typ.	10	dB
Intercept point 3 rd Order typ.		dBm
RF connectors	N female and N female	
Cooling	Forced air (self-contained fans)	
Operating temperature Range	0 °C ... + 40	° C
Power Supply	230 AC +/- 10 % ,47-63 Hz	V
Dimensions (W x L x H)	4 U 19" Rack p 460 mm	mm

All data at room temperature + 22 °C, into 50 Ohms, subject to change without notice

Made in European Union

18/7/01

R.F.P.A. S.A.

Parc d'activité de Fontaudin F33370 Artigues près Bordeaux
 France Tél : +33 (0)5 56 86 85 84 Fax: + 33 (0) 5 56 86 55 56